

MINI Series

- Constant Voltage • Current Operation Mode
- 최대 300V • 400mA • 60W (MINI-300)
- 최대 500V • 400mA • 120W (MINI-500)
- 2pair 출력 단자
- 가볍고 컴팩트한 디자인
- 합리적인 가격
- 2단계의 프로그램 제어



MINI-300



MINI-500

MP Series

- 4pair 출력 단자
- 모든 파라미터를 확인할 수 있는 2.4" TFT-LCD 컬러 화면
- 컴팩트 사이즈
- Constant Voltage • Current • Power Operation Mode
- DNA, RNA, 단백질 전기영동 및 블러팅(Blotting) 등 다양하게 사용 가능
- 최대 6 단계의 프로그램 제어



MP-310



MP-320



MP-510


SPECIFICATIONS

Model	MINI-300	MINI-500	MP-310	MP-320	MP-510
Display	LED		2.4" TFT LCD		
Output Voltage	10 - 300V	10 - 500V	5 - 300V	5 - 300V	5 - 500V
Output Current	10 - 400mA	1 - 400mA	1 - 700mA	10 - 3,000mA	1 - 800mA
Output Power	60W	120W	150W	300W	300W
Output Type	Constant Voltage / Current		Constant Voltage / Current / Power		
Timer	999 (min) with alarm / continuous (set=0)		Constant: 9999 (min) with alarm / continuous Program: 999 (min) with alarm / continuous		
Rated Voltage	100 - 240V~, 50-60Hz, 2A	100 - 240V~, 50-60Hz, 2.5A	100-240V~; 47-60Hz	100-240V~; 47-60Hz	100-240V~; 47-60Hz
Program	2-STEP Program		Program Storage: 30 programmed files Program Multi-Step: Up to 6 steps		
Dimension	140W x 191L x 84Hmm		215W x 335L x 104Hmm		
Weight	Approx. 1kg		Approx. 2.1kg		


FOR MP SERIES




Stackable case



Constant mode



Program mode



Typical running mode